

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190501-R25568  
**Report Reference** R25568-20141224  
**Issue Date** 2019-MAY-01

**Issued to:** NATIONAL GUARD PRODUCTS INC  
4985 E RAINES RD  
MEMPHIS TN 38118-7024

**This certificate confirms that representative samples of** MISCELLANEOUS FIRE DOOR ACCESSORIES;  
MISCELLANEOUS FIRE DOOR ACCESSORIES,  
POSITIVE-PRESSURE TESTED  
See addendum page.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** ANSI/UL 10C, Positive Pressure of Fire Tests of Door Assemblies, ANSI/UL 10B, Fire Tests of Door Assemblies, and CAN/ULC-S104, Standard Method for Fire Tests of Door Assemblies

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20190501-R25568  
**Report Reference** R25568-20141224  
**Issue Date** 2019-MAY-01

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

NGP-Edge® Sealing System, Model 9250, intumescent door bottom shoe, rated up to and including 20 minutes. May include additional suffix letters: A, DKB, N, NF, T, V, WH.

NGP-Edge® Sealing System, Model 9245, intumescent door bottom shoe, rated up to and including 3/4 hour. May include additional suffix letters: A, DKB, N, NF, T, V, WH.

NGP-Edge® Sealing System, Models 9290, 9490, and 9590 Intumescent Door Bottom Seals, rated up to and including 1-1/2 hr.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

