For the complete list of GapGuard Fire Door Accessories, the most up-to-date product information and installation instructions, scan the QR code or **visit ngp.com**.

GAPGUARD

Fire Door Accessories

PRODUCT OVERVIEW

GapGuard Fire Door Accessories are UL Certified for use on Hollow Metal and Wood Fire-Rated Doors

UL CERTIFIED FOR USE IN THE US AND CANADA

GAP90

Fire Door Head/Jamb Gap Solution

- ⅛" - 9⁄16" Gaps on 20-180 Minute Doors
- Non-Handed
- In-Field Modifiable
- Available in Dark Brown and Gray

180 MINUTES

Required When Gap90-ME is Applied on Wood Doors Only

GAP90-ME

Meeting Edge and Perimeter Gap Solution

- Application Certified for Perimeter of Fire Doors and/or on Frames with Excessive Clearance up to ⅜"
- Non-Handed
- In-Field Modifiable
- Gray Finish

90 MINUTES

9590

Fire Door Bottom Gap Solution

- Door Bottom Gaps, Measuring up to 1½"
- Non-Handed
- In-Field Modifiable
- Brushed Stainless Steel Finish

180 MINUTES

9990

Fire Door Top Gap Solution

- Door Top Gaps, Measuring up to ½"
- Non-Handed
- In-Field Modifiable
- Recommended for Doors with Parallel Arm Closers
- Brushed Stainless Steel Finish

180 MINUTES

GAPGUARD

UL CERTIFIED FOR USE IN THE US AND CANADA

PRODUCT OVERVIEW (continued)

9595DKB

90 MINUTES

Floating Fire Door Bottom Gap Solution

- Door Bottom Gaps, up to 1⅜"
- Non-Handed
- Designed to Travel Over Uneven Floors, With a Range of ⅜"
- Optional L-Bracket Allows for Easy Installation
- Powder-Coated Matte-Black

9200

45 MINUTES | 60 MINUTES

Gap Solution for Excessive Fire Door and Frame Clearances

- For Excessive Gaps up to ⅜", up to 45 Minutes
- For excessive gaps up to 5⁄16" at 60 min.
- Dimensions are 1" x 1⁄16"
- Formulated to Expand at 275° up to 20 Times Original Thickness
- Sold by the Foot: 3' Minimum to 410' Reel

9245

45 MINUTES

Intumescent Door Shoe

- For Excessive Gaps up to 1½", 45 Min.
- Door Shoe Available with Vinyl Seal (V) or Nylon Brush (WH)
- **Anodized:** 9245VA / 9245WHA
  Black Anodized: 9245VB / 9245WHB
  Dark Bronze: 9245VDKB / 9245WHDKB

FR180-6, FR180-48

180 MINUTES

Frame Repair Kit

- UL-Certified for Steel Fire Doors and Frames Rated up to 180 Min.
- FR180-6: 6" Kits, 5 per Box
  FR180-48: 48" Kits, (Can be Cut Down in Field) 5 per Box

9545

45 MINUTES

Excessive Clearance Door Bottom

- For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- For Excessive Gaps up to 1½", 45 Min.
- **Anodized:** 9545VA / 9545WHA
  Black Anodized: 9545VB / 9545WHB
  Dark Bronze: 9545VDKB / 9545WHDKB

FP180-225

180 MINUTES

Frame Patch Kit

- UL-Certified for Steel Fire Doors and Frames Rated up to 180 Minutes
- Maximum Area of Cutout Concealed by Frame Patch is 2½" Sq. In.

9220

20 MINUTES

Excessive Clearance Door Bottom

- For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- For Excessive Gaps up to 1½", 20 Min.
- **Anodized:** 9220VA / 9220WHA
  Black Anodized: 9220VB / 9220WHB
  Dark Bronze: 9220VDKB / 9220WHDKB

GAPGUARD FIRE CAULK

90 MINUTES

- For Holes up to 1¾" Diameter on Doors and Frames up to 90 minutes
- GAPGUARD FIRE CAULK 10.0 oz Cartridges, 10 per Box
- GAP FIRE CAULK 3.0 oz. Tubes, 6 per Box

MEMPHIS | CARSON CITY

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874
Email: info@ngp.com

Quotes: quotes@ngp.com
Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH