

CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210416
Date 2021-May-06

Issued to: NATIONAL GUARD PRODUCTS INC
4985 E RAINES RD
MEMPHIS TN, 38118-7024 US

**This is to certify that
representative samples of**

MISCELLANEOUS FIRE DOOR ACCESSORIES
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 10C-Positive Pressure Fire Tests of Door
Assemblies

ANSI/UL 10B-Fire Tests of Door Assemblies

CAN/ULC-S104-15-Standard Method for Fire Tests of Door
Assemblies

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210416
Date 2021-May-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Models:

USC, CNC Model GapGuard Fire Caulk - Fire Door Caulk, for installation per manufacturer's instructions, to fill through-holes present in steel frames, steel and wood composite core doors, rated up to and including 1-1/2 hour.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210417
Date 2021-May-06

Issued to: NATIONAL GUARD PRODUCTS INC
4985 E RAINES RD
MEMPHIS TN, 38118-7024 US

**This is to certify that
representative samples of**

MISCELLANEOUS FIRE DOOR ACCESSORIES
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 10C-Positive Pressure Fire Tests of Door
Assemblies

ANSI/UL 10B-Fire Tests of Door Assemblies

CAN/ULC-S104-15-Standard Method for Fire Tests of Door
Assemblies

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210417
Date 2021-May-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Models:

USC, CNC Models HP90-0.5, HP90-1.0, HP90-1.5, HP90-2.0, HP90-2x6, HP90-4x6, HP90-CYL KIT, HP90-MORT KIT, HP90-FB KIT and HP90-SOLUTION KIT Hardware Plug System, for installation per manufacturer's instructions, to fill through-holes and machined hardware openings present in steel and wood composite core doors, rated up to and including 1-1/2 hour.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



Certificate of Compliance

Certificate Number:
R25568

Report Reference:
R25568-20141223

Issue Date:
2024-12-30

Issued to:

**National Guard Products, Inc.
4985 E RAINES RD
MEMPHIS TN, 38118-7024 United States**

This certificate confirms that representative samples of:

MISCELLANEOUS FIRE DOOR ACCESSORIES

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 10B, Fire Tests of Door Assemblies
UL 10C, Positive Pressure Fire Tests of Door, Assemblies
CAN/ULC-S104-15-R2020, Standard Method for Fire Tests of
Door Assemblies**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number R25568
Report reference R25568-20141223
Date 2024-12-30

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

NGP-Edge® Sealing System, Model 9200, self-adhesive intumescent seal and Model 9275/9225, Strike shims rated up to and including 45 minutes. May include additional suffix letters: DKB

Model 9990 Intumescent Door Cap System for use with 1-1/2 hr swinging type fire doors.

NGP-Edge® Sealing System, GAP90 consisting of Models 9400, 9945, 5075, and Model 9275/9225, Strike shims rated up to and including 1-1/2 hour. May include use of Model SS306 in 3/4 hour applications. May include additional suffix letters: B, CL, DKB, W.

NGP-Edge® Sealing System, GAP90N consisting of Models 9400, 9945N, 5075, and Model 9275/9225, Strike shims rated up to and including 1-1/2 hour. May include use of Model SS306 in 3/4 hour applications. May include additional suffix letters: B, CL, DKB, W.

NGP-Edge® Sealing System, GAP90 consisting of Models 9400, 9945, and 5075, for use with RIM Type Fire-exit hardware, rated up to and including 1-1/2 hour.

NGP-Edge® Sealing System, GAP90N consisting of Models 9400, 9945N, and 5075, for use with RIM Type Fire-exit hardware, rated up to and including 1-1/2 hour.

NGP-Edge® Sealing System, GAP90N consisting of Models 9400, 9945N, and 5075, is for use on UL Certified Fire Doors and Frames rated up to and including 1-1/2 hour.

NGP-Edge® Sealing System, GAP90-ME Metal Edge, in combination with Gap Guard Fire Caulk, is for use on UL Certified Fire Doors and Frames rated up to and including 1-1/2 hour for excessive gaps up to 3/8 in. It shall be used at only one location on single swinging and pair of swinging type fire-rated wood or steel doors, and on hollow metal frames as stated per the installation instructions in ILL I.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210415
Date 2021-May-06

Issued to: NATIONAL GUARD PRODUCTS INC
4985 E RAINES RD
MEMPHIS TN, 38118-7024 US

**This is to certify that
representative samples of**

MISCELLANEOUS FIRE DOOR ACCESSORIES
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 10C-Positive Pressure Fire Tests of Door
Assemblies

ANSI/UL 10B-Fire Tests of Door Assemblies

CAN/ULC-S104-15-Standard Method for Fire Tests of Door
Assemblies

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R25568
Report Reference R25568-20210415
Date 2021-May-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Models:

USC, CNC NGP-Edge® Sealing System, Model 9595 Fire Door Bottom for use with UL Classified steel composite, hollow metal, wood and plastic-covered composite core single swing doors rated up to and including 1-1/2 hour and UL Listed wood core single swing doors rated up to 20 minutes.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



Certificate of Compliance

Certificate Number:
R25568

Report Reference:
R25568-20141224

Issue Date:
2025-02-06

Issued to:

**National Guard Products, Inc.
4985 E RAINES RD
MEMPHIS TN, 38118-7024 United States**

This certificate confirms that representative samples of:

MISCELLANEOUS FIRE DOOR ACCESSORIES

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

ANSI/UL 10C, Positive Pressure of Fire Tests of Door Assemblies, ANSI/UL 10B, Fire Tests of Door Assemblies, and CAN/ULC-S104, Standard Method for Fire Tests of Door Assemblies

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number R25568
Report reference R25568-20141224
Date 2025-02-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

NGP-Edge® Sealing System, Model 9250, intumescent door bottom shoe, rated up to and including 20 minutes. May include additional suffix letters: A, DKB, N, NF, T, V, WH.

NGP-Edge® Sealing System, Model 9245, intumescent door bottom shoe, rated up to and including 3/4 hour. May include additional suffix letters: A, DKB, N, NF, T, V, WH.

NGP-Edge® Sealing System, Models 9590 Intumescent Door Bottom Seals, rated up to and including 1-1/2 hr.

NGP-Edge® Sealing System, Model 9545, intumescent door bottom shoe, rated up to and including 45 minutes.

NGP-Edge® Sealing System, Model 9220, intumescent door bottom shoe, rated up to and including 20 minutes with and without hose stream.



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:
R25568

Report Reference:
R25568-20241127

Issue Date:
2024-12-05

Issued to:

**National Guard Products, Inc.
4985 E RAINES RD
MEMPHIS TN, 38118-7024 United States**

This certificate confirms that representative samples of:

MISCELLANEOUS FIRE DOOR ACCESSORIES

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

See Addendum Page for Standard (s)

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink that reads 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number R25568
Report reference R25568-20241127
Date 2024-12-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

MODELS:

FP180-225 frame patch kits and FR180 frame repair kits up to 48 in. long rated for 3 hours.

Safety of Standard(s):

UL 10B, Fire Tests of Door Assemblies

UL 10C, Positive Pressure Fire Tests of Door Assemblies

CAN/ULC-S104-15-R202, Standard Method for Fire Tests of Door Assemblies



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

Certificate of Compliance

Certificate Number:
R25568

Report Reference:
R25568-20250204

Issue Date:
2025-02-06

Issued to:

**National Guard Products, Inc.
4985 E RAINES RD
MEMPHIS TN, 38118-7024 United States**

This certificate confirms that representative samples of:

MISCELLANEOUS FIRE DOOR ACCESSORIES

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 10B Fire Tests of Door Assemblies, UL 10C Positive Pressure Fire tests of Door Assemblies
CAN/ULC-S104-15-R2020 Standard Method for Fire Tests of Door Assemblies**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch
UL Mark Certification Program Owner

CERTIFICATE OF COMPLIANCE

Certificate number R25568
Report reference R25568-20250204
Date 2025-02-06

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Series HP90CNC Conversion Plate and Wrap Kit rated up to 1-1/2 hours, and consisting of the following Models:

- HP90CNC-1000 - Mortise or Cylindrical Lock Blank out Kit Plate(s)
- HP90CNC-1100 - Mortise or Cylindrical Lock Blank out Kit Wrap
- HP90CNC-2000 – Mortise to Cylindrical Lock Conversion Plate Kit
- HP90CNC-2100 - Mortise to Cylindrical Lock Conversion Kit Wrap
- HP90CNC-3100 - Cylindrical to Mortise Lock Conversion Kit Wrap
- HP90CNC-4100 - Cylindrical to Cylindrical Lock Repair Kit Wrap
- HP90CNC-5000 – Mortise Lock Conversion Kit Plate
- HP90CNC-5100 – Mortise Lock Conversion Kit Wrap
- HP90CNC-6000 - Fire Exit Hardware Conversion Kit Plate
- HP90CNC-6100 - Fire Exit Hardware Conversion Kit Wrap



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.