



GAPGUARD

Fire Door Accessories

PRODUCT OVERVIEW

GapGuard Fire Door Accessories are UL Certified for use on Hollow Metal and Wood Fire-Rated Doors

For the complete list of GapGuard Fire Door Accessories, the most up-to-date product information and installation instructions, scan the QR code or visit ngp.com.



UL CERTIFIED FOR USE IN THE US AND CANADA



GAP90 Fire Door Head/Jamb Gap Solution

- 1/8" - 3/8" Gaps on 60 & 90 Minute Doors
- 1/8" - 9/16" Gaps on 20 & 45 Minute Doors
- Non-Handed
- In-Field Modifiable
- Available in Dark Brown and Gray

ALTERNATE 5050 PLACEMENT LOCATIONS:



Required When Gap90-ME is Applied on Wood Doors Only


GAP90-ME Meeting Edge and Perimeter Gap Solution

- Application Certified for Perimeter of Fire Doors and/or on Frames with Excessive Clearance up to 3/8"
- Non-Handed
- In-Field Modifiable
- Gray Finish



9590 Fire Door Bottom Gap Solution

- Door Bottom Gaps, Measuring up to 1 1/2"
- Non-Handed
- In-Field Modifiable
- Brushed Stainless Steel Finish



9990 Fire Door Top Gap Solution

- Door Top Gaps, Measuring up to 1/2"
- Non-Handed
- In-Field Modifiable
- Recommended for Doors with Parallel Arm Closers
- Brushed Stainless Steel Finish

GAPGUARD

UL CERTIFIED FOR USE IN
THE US AND CANADA



PRODUCT OVERVIEW (continued)

9595DKB
Floating Fire Door
Bottom Gap Solution 90
MINUTES

- ▶ Door Bottom Gaps, up to 1 3/8"
- ▶ Non-Handed
- ▶ Designed to Travel Over Uneven Floors, With a Range of 3/8"
- ▶ Optional L-Bracket Allows for Easy Installation
- ▶ Powder-Coated Matte-Black



9200
Gap Solution for
Excessive Fire Door and
Frame Clearances 45
MINUTES

- ▶ For Excessive Gaps up to 3/8", up to 45 Minutes
- ▶ Dimensions are 1" x 1/16"
- ▶ Formulated to Expand at 275° up to 20 Times Original Thickness
- ▶ Sold by the Foot: 3' Minimum to 410' Reel



9245
Intumescent Door Shoe 45
MINUTES

- ▶ For Excessive Gaps up to 1 1/2", 45 Min.
- ▶ Door Shoe Available with Vinyl Seal (V) or Nylon Brush (WH)
- ▶ **Anodized:** 9245VA / 9245WHA
Black: 9245VDKB / 9245WHDKB




Provided End Caps

FR180
Frame Repair Kit 180
MINUTES

- ▶ UL-Certified for Steel Fire Doors and Frames Rated up to 180 Min.
- ▶ Available in 6" and 48" Sizes and May be Field Cut to Size



FR180-6
FR180-48

9545
Excessive Clearance
Door Bottom 45
MINUTES

- ▶ For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- ▶ For Excessive Gaps up to 1 1/2", 45 Min.
- ▶ **Anodized:** 9545VA / 9545WHA
Black: 9545VDKB / 9545WHDKB




Provided End Caps

FP180-225
Frame Patch Kit 180
MINUTES

- ▶ UL-Certified for Steel Fire Doors and Frames Rated up to 180 Minutes
- ▶ Maximum Area of Cutout Concealed by Frame Patch is 2 1/2" Sq. In.



9220
Excessive Clearance
Door Bottom 20
MINUTES

- ▶ For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- ▶ For Excessive Gaps up to 1 1/2", 20 Min.
- ▶ **Anodized:** 9220VA / 9220WHA
Black: 9220VDKB / 9220WHDKB




Provided End Caps

GAPGUARD FIRE CAULK 45
MINUTES 90
MINUTES

- ▶ For Holes up to 1/2" Diameter on 60 & 90 Minute Doors
- ▶ For Holes up to 1" Diameter on 20 & 45 Minute Doors
- ▶ 10.0 oz Cartridges, 10 per Box
- ▶ 3.0 oz. Tubes, 6 per Box



10.0 oz. Cartridge
3.0 oz. Tube

NGP-GAP-QUI-0326-A



MEMPHIS | CARSON CITY

NATIONAL GUARD PRODUCTS, INC.

MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706

Fax: (800) 255-7874
Email: info@ngp.com

Quotes: quotes@ngp.com
Orders: orders@ngp.com

ngp.com
1-800-NGP-RUSH