



# GAPGUARD

Fire Door Accessories

## PRODUCT OVERVIEW

GapGuard Fire Door Accessories are UL Certified for use on Hollow Metal and Wood Fire-Rated Doors

For the complete list of GapGuard Fire Door Accessories, the most up-to-date product information and installation instructions, scan the QR code or visit [ngp.com](http://ngp.com).



UL CERTIFIED FOR USE IN THE US AND CANADA



**GAP90**  
Fire Door Head/Jamb Gap Solution

- 1/8" - 9/16" Gaps on 20-180 Minute Doors
- Non-Handed
- In-Field Modifiable
- Available in Dark Brown and Gray

ALTERNATE 5075 PLACEMENT LOCATIONS:




**GAP90-ME**  
Meeting Edge and Perimeter Gap Solution


 Required When Gap90-ME is Applied on Wood Doors Only

- Application Certified for Perimeter of Fire Doors and/or on Frames with Excessive Clearance up to 3/8"
- Non-Handed
- In-Field Modifiable
- Gray Finish





**9590**  
Fire Door Bottom Gap Solution

- Door Bottom Gaps, Measuring up to 1 1/2"
- Non-Handed
- In-Field Modifiable
- Brushed Stainless Steel Finish

**9990**  
Fire Door Top Gap Solution

- Door Top Gaps, Measuring up to 1/2"
- Non-Handed
- In-Field Modifiable
- Recommended for Doors with Parallel Arm Closers
- Brushed Stainless Steel Finish



# GAPGUARD

UL CERTIFIED FOR USE IN  
THE US AND CANADA



## PRODUCT OVERVIEW (continued)

### 9595DKB

#### Floating Fire Door Bottom Gap Solution



**90 MINUTES**

- ▶ Door Bottom Gaps, up to 1 3/8"
- ▶ Non-Handed
- ▶ Designed to Travel Over Uneven Floors, With a Range of 3/8"
- ▶ Optional L-Bracket Allows for Easy Installation
- ▶ Powder-Coated Matte-Black

### 9200

#### Gap Solution for Excessive Fire Door and Frame Clearances



**45 MINUTES** **60 MINUTES**

- ▶ For Excessive Gaps up to 3/8", up to 45 Minutes
- ▶ For excessive gaps up to 5/16" at 60 min.
- ▶ Dimensions are 1" x 1/16"
- ▶ Formulated to Expand at 275° up to 20 Times Original Thickness
- ▶ Sold by the Foot: 3' Minimum to 410' Reel

### 9245

#### Intumescent Door Shoe



**45 MINUTES**

- ▶ For Excessive Gaps up to 1 1/2", 45 Min.
- ▶ Door Shoe Available with Vinyl Seal (V) or Nylon Brush (WH)
- ▶ **Anodized:** 9245VA / 9245WHA  
**Black:** 9245VDKB / 9245WHDKB

Provided End Caps

### FR180

#### Frame Repair Kit



**180 MINUTES**

- ▶ UL-Certified for Steel Fire Doors and Frames Rated up to 180 Min.
- ▶ Available in 6" and 48" Sizes and May be Field Cut to Size

FR180-6  
FR180-48

### 9545

#### Excessive Clearance Door Bottom



**45 MINUTES**

- ▶ For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- ▶ For Excessive Gaps up to 1 1/2", 45 Min.
- ▶ **Anodized:** 9545VA / 9545WHA  
**Black:** 9545VDKB / 9545WHDKB

Provided End Caps

### FP180-225

#### Frame Patch Kit



**180 MINUTES**

- ▶ UL-Certified for Steel Fire Doors and Frames Rated up to 180 Minutes
- ▶ Maximum Area of Cutout Concealed by Frame Patch is 2 1/2" Sq. In.

### 9220

#### Excessive Clearance Door Bottom



**20 MINUTES**

- ▶ For Use on UL10B and UL10C Wood or Hollow Metal Fire Doors
- ▶ For Excessive Gaps up to 1 1/2", 20 Min.
- ▶ **Anodized:** 9220VA / 9220WHA  
**Black:** 9220VDKB / 9220WHDKB

Provided End Caps

### GAPGUARD FIRE CAULK



**90 MINUTES**

- ▶ For Holes up to 1 3/4" Diameter on Doors and Frames up to 90 minutes
- ▶ 10.0 oz Cartridges, 10 per Box
- ▶ 3.0 oz. Tubes, 6 per Box

10.0 oz. Cartridge  
3.0 oz. Tube

NGP-GAP-QUI-0526-A



MEMPHIS | CARSON CITY

## NATIONAL GUARD PRODUCTS, INC.

**MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706

**Fax:** (800) 255-7874

**Email:** info@ngp.com

**Quotes:** quotes@ngp.com

**Orders:** orders@ngp.com

**ngp.com**  
**1-800-NGP-RUSH**