



# 127S

## Silicone Closed Cell Sponge Seal

### PRODUCT CUT SHEET

#### Material


Aluminum Alloy 6063, T5 Temper  
Synthetic Rubber Polymer: Siloxane Closed Cell Sponge  
Silicone Sponge is Black

- ▶ Excellent Flexibility and Memory
- ▶ Flame-Resistant
- ▶ Moisture-Resistant
- ▶ Temperature Range -100°F to 500°F, Remains Flexible at Extreme Temperatures
- ▶ Excellent Resistance to Ozone, UV and Aging
- ▶ Recommended for Areas Using FM200 or Halon Fire Suppression Systems
- ▶ BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- ▶ #6 x 3/4" Stainless Steel Sheet Metal Screws Furnished
- ▶ Screw Holes Slotted for Adjustment
- ▶ Patent Pending Microcellular Silicone

#### Finishes

127SA Anodized Aluminum  
127SDKB Dark Bronze

PROJECT:
SUBMITTED BY:
DATE:
NOTES:



NGP-GKT-127S-PCS-1223-A

#### NATIONAL GUARD PRODUCTS, INC.

##### MEMPHIS

4985 East Raines Road  
Memphis, TN 38118

##### CARSON CITY

3689 Arrowhead Drive  
Carson City, NV 89706

Fax: (800) 255-7874

Email: [info@ngp.com](mailto:info@ngp.com)

Quotes: [quotes@ngp.com](mailto:quotes@ngp.com)

Orders: [orders@ngp.com](mailto:orders@ngp.com)

**ngp.com**  
1-800-NGP-RUSH