



# 137N

## Neoprene Smoke-Rated Astragal Seal Set

### PRODUCT CUT SHEET

PROJECT:
SUBMITTED BY:
DATE:
NOTES:


#### Material

Aluminum Alloy 6063, T5 Temper  
Synthetic Rubber Polymer Blend: Chloroprene and EPDM  
Neoprene is Black

- ▶ Very Good Abrasion Resistance, Tensile Strength and Memory
- ▶ Flame Resistant
- ▶ Moisture Resistant
- ▶ Temperature Range -20°F to 200°F
- ▶ Good Resistance To Ozone, Sunlight and Aging
- ▶ Fire-Rated Astragal Seals Cannot Replace Any Astragal Required on the Door by the Door Manufacturer to Maintain Its Fire Label
- ▶ IBC, NFPA 80, NFPA105, and NFPA 252 Require the Gap at the Meeting Edge Between Fire Labeled Doors Must Not Exceed  $\frac{1}{8}$ "
- ▶ #6 x  $\frac{3}{4}$ " Stainless Steel SMS Furnished
- ▶ Screw Holes Slotted for Adjustment
- ▶ Order as Set to Receive Two Pieces

#### Finishes

137NA Anodized Aluminum  
137NB Gold  
137NDKB Dark Bronze



NGP-GKT-137NSET-PCS-1120-A