




# 158

## Astragal Seals



See [ngp.com](http://ngp.com) for  
All Applicable  
Certifications for  
this Product.

158N, 158S, 158V (ONLY)



POSITIVE PRESSURE  
TESTED GASKETING  
MATERIALS FOR  
FIRE DOORS FOR  
APPLICATION TO  
HOLLOW-METAL-  
TYPE FIRE DOORS  
RATED UP TO 3  
HOURS AND WOOD-  
TYPE FIRE DOORS  
RATED UP TO  
1½ HOURS.  
CATEGORY J

# S

# M

# A

# F

[ngp.com](http://ngp.com)

1-800-NGP-RUSH

FAX:

(800) 255-7874

QUOTES:


[quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS:

[orders@ngp.com](mailto:orders@ngp.com)



## INSTALLATION INSTRUCTIONS



# 158

1. Cut astragal to length.
2. Place astragal as shown above, with gasketing slightly compressed.
3. Mark screw holes.
4. Drill pilot holes with a  $\frac{7}{64}$ " bit.
5. Install with screws provided, working from one end to the other.
6. Adjust astragal so it does not impede closing and latching of doors.

**ngp.com**

**1-800-NGP-RUSH**

FAX: (800) 255-7874

QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

### **NGP MEMPHIS**

4985 East Raines Road

Memphis, TN 38118

### **CARSON CITY**

3689 Arrowhead Drive

Carson City, NV 89706