


# NCP T70

Perimeter Seal with  
Concealed Fastener



# SEAL



**BHMA**  
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS  
FOR FIRE DOORS FOR APPLICATION TO HOLLOW-  
METAL-TYPE FIRE DOORS RATED UP TO 3 HOURS  
AND WOOD-TYPE FIRE DOORS RATED UP TO 1½  
HOURS, CATEGORY H

SILICONE AND NEOPRENE ARE SMOKE  
AND DRAFT CONTROL GASKETING  
(CATEGORY H) TESTED TO UL 1784;  
MEETS REQUIREMENTS OF NFPA 105,  
IBC FOR USE ON "S" LABEL DOORS.

- Aluminum Alloy 6063, T5 Temper
- Flame/Moisture Resistant
- #6 X ¾" Stainless Steel Sheet Metal Screws Furnished

**ngp.com**

**1-800-NCP-RUSH**


See [ngp.com](http://ngp.com) for All Applicable  
Certifications for this Product.

---

# INSTALLATION INSTRUCTIONS

---

## 170



1. Cut seal to fit.
2. With door closed, position seal, mark screw holes.
3. Drill pilot holes for screws using a  $\frac{7}{64}$ " drill bit.
4. Install with screws provided in all mounting holes, working from one end to the other.
5. Adjust position so that gasket is slightly compressed against door but does not impede proper closing and latching.



[ngp.com](http://ngp.com)

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

### **MEMPHIS**

4985 East Raines Road  
Memphis, TN 38118

### **CARSON CITY**

3689 Arrowhead Drive  
Carson City, NV 89706