


NGFP 18V

Smooth Vinyl Door Shoe



POSITIVE PRESSURE TESTED GASKETING

MATERIALS FOR FIRE DOORS

FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS RATED UP TO 3 HOURS AND WOOD-TYPE

FIRE DOORS RATED UP TO 1½ HOURS.

CATEGORY H



SMOKE AND DRAFT CONTROL

GASKETING (CATEGORY H) TESTED TO

UL 1784; MEETS REQUIREMENTS OF NFPA 105, IBC FOR USE ON "S" LABEL

DOORS.

DOORS.

- Aluminum Alloy 6063, T5 Temper
- Vinyl is Black
- Temp. Range: 0°F-140°F


- Flame/Moisture Resistant
- #6 X ¾" Stainless Steel Sheet Metal Screws Furnished
- Economical

SEAL

ngfp.com
1-800-NGFP-RUSH

INSTALLATION INSTRUCTIONS

18V



1. Measure and cut door shoe to fit.
2. Crimp or stake metal retainer at both sides and both ends to prevent gasket from migrating during use.
3. Items with drip cap should be notched to clear stops on jambs before installation.
4. Position seal on door with gasket compressed $\frac{1}{16}$ " against sill.
5. Mark screw holes.
6. Drill pilot holes for screws using $\frac{7}{64}$ " drill bit.
7. Install with screws provided.
8. Adjust position so that gasket does not impede proper closing and latching of door.



ngp.com

1-800-NGP-RUSH

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com

NGP MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706