


The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-like shape with a pointed top and a pointed bottom. This shield is centered on a solid blue rectangular background.

# 410

## Smooth Surface Threshold



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 2 ½" Wide x ¼" Tall
- ▶ Smooth Top
- ▶ Typical Wall Thickness: .125"
- ▶ Weight: .36 Lb/Ft.
- ▶ #10 x 1 ½" FH Zinc Plated Wood Screws Included



**BHMA**  
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1½ HOURS. CATEGORY J

# THRESHOLD

**ngp.com**  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: quotes@ngp.com


11.24

---

# INSTALLATION INSTRUCTIONS

---

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



**NGP**

THE PRODUCTS  
**YOU COUNT ON**  
THE PEOPLE  
**YOU TRUST**  
**ngp.com**

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706