


The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-like shape with a pointed top and a slightly curved bottom. This shield is centered on a solid blue rectangular background.

457

Half Saddle Threshold



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ Fluted Top
- ▶ 5" Wide x 3/4" Tall
- ▶ #10 x 1 1/2" FH Zinc Plated Wood Screws Included. Dark Bronze Supplied With DKB Thresholds
- ▶ Typical Wall Thickness: 0.125"
- ▶ Weight: 0.79 Lbs./Ft.
- ▶ Mill or Dark Bronze Finish
- ▶ Optional Slip Resistant SIA Finish

THRESHOLD

BHMA
CERTIFIED



See ngp.com for All Applicable Certifications for this Product.



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS RATED UP TO 1-1/2 HOURS. CATEGORY J

ngp.com

1-800-NGP-RUSH


FAX: (800) 255-7874

QUOTES: quotes@ngp.com

8.24

INSTALLATION INSTRUCTIONS

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST
ngp.com

FAX: (800) 255-7874
QUOTES: quotes@ngp.com
ORDERS: orders@ngp.com

NGP MEMPHIS
4985 East Raines Road
Memphis, TN 38118

CARSON CITY
3689 Arrowhead Drive
Carson City, NV 89706