


The NGP logo consists of the letters "NGP" in a bold, blue, sans-serif font. The letters are contained within a white, shield-like shape with a pointed top and a slightly curved bottom. This white shape is centered on a solid blue rectangular background.

613BR

Architectural Bronze
1/4" Saddle Threshold
1/4" x 6"



- ▶ Alloy CDA 385
(Copper Alloy No. C38500)
- ▶ 6" Wide x 1/4" Tall
- ▶ Fluted Top
- ▶ Typical Wall Thickness: .157"
- ▶ Weight: 3.06 Lbs./Ft.
- ▶ #10 x 1 1/2" Brass Wood Screws Included. Antique Bronze Finish Screws Provided With Dark Bronze Threshold



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1 1/2 HOURS. CATEGORY J

ngp.com
1-800-NGP-RUSH

FAX: (800) 255-7874
QUOTES: quotes@ngp.com

3.25

THRESHOLD

INSTALLATION INSTRUCTIONS




WARNING:

This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and/or developmental and reproductive harm.

For more information, go to P65Warnings.ca.gov.

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



THE PRODUCTS
YOU COUNT ON
THE PEOPLE
YOU TRUST

ngp.com

FAX: (800) 255-7874

QUOTES: quotes@ngp.com

ORDERS: orders@ngp.com

NGP MEMPHIS

4985 East Raines Road
Memphis, TN 38118

CARSON CITY

3689 Arrowhead Drive
Carson City, NV 89706