




# NGP

## 613HD

Aluminum  
Heavy-Duty  
Threshold  
1/4" x 6"



- ▶ Aluminum Alloy 6063, T5 Temper
- ▶ 6" Wide x 1/4" Tall
- ▶ Fluted Top
- ▶ BHMA Certified to ANSI/BHMA A156.21 10,000 Lb. Load Test
- ▶ Typical Wall Thickness: .244"
- ▶ Weight: 1.66 Lbs./Ft.
- ▶ #10 x 1 1/2" FH Zinc Plated Wood Screws Included



**BHMA**  
CERTIFIED



POSITIVE PRESSURE TESTED GASKETING MATERIALS FOR FIRE DOORS. FOR APPLICATION TO HOLLOW-METAL-TYPE FIRE DOORS, RATED UP TO 3 HOURS AND WOOD-TYPE FIRE DOORS, RATED UP TO 1 1/2 HOURS. CATEGORY J

# THRESHOLD

**ngp.com**  
1-800-NGP-RUSH

FAX: (800) 255-7874  
QUOTES: quotes@ngp.com

11.24

---

# INSTALLATION INSTRUCTIONS

---

1. Cut threshold to size required.
2. Notch around door frame if desired.
3. Attach to floor surface with fasteners provided.
4. Caulk around base of threshold for moisture control.



---

THE PRODUCTS  
**YOU COUNT ON**  
THE PEOPLE  
**YOU TRUST**  
**ngp.com**

---

FAX: (800) 255-7874  
QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)  
ORDERS: [orders@ngp.com](mailto:orders@ngp.com)

**NGP MEMPHIS**  
4985 East Raines Road  
Memphis, TN 38118

**CARSON CITY**  
3689 Arrowhead Drive  
Carson City, NV 89706