



9115

ALLSEAL® SMOKE-RATED ASTRAGAL SEAL SET

PRODUCT CUT SHEET

PROJECT:
SUBMITTED BY:
DATE:
NOTES:



Material

Aluminum Alloy 6063, T5 Temper
Synthetic Rubber Polymer: Siloxane Closed Cell Sponge
Silicone Plus is Tan

- ▶ Premium Grade Seals Specially Formulated to Withstand Greater Temperature Extremes While Providing Maximum Protection Against Air Infiltration
- ▶ Excellent Flexibility and Memory
- ▶ Flame Resistant
- ▶ Moisture Resistant
- ▶ Temperature Range -100°F to 500°F, Remains Flexible at Extreme Temperatures
- ▶ Excellent Resistance to Ozone, UV and Aging
- ▶ Recommended for Areas Using FM200 or Halon Fire Suppression Systems
- ▶ BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- ▶ Fire-Rated Astragal Seals Cannot Replace Any Astragal Required on the Door by the Door Manufacturer to Maintain Its Fire Label
- ▶ IBC, NFPA 80, NFPA105, and NFPA 252 Require the Gap at the Meeting Edge Between Fire Labeled Doors Must Not Exceed 1/8"
- ▶ #6 x 3/4" Stainless Steel SMS Furnished
- ▶ Screw Holes Slotted for Adjustment
- ▶ Provided as Two Piece Set

Finishes

9115A Anodized Aluminum
9115B Gold
9115DKB Dark Bronze



NGP-GKT-9115-PCS-0720-A