



# 9500 X 2525

NPG-Edge® Intumescent Fire Seal x Smoke Seal


## PRODUCT CUT SHEET

PROJECT:
SUBMITTED BY:
DATE:
NOTES:

### Material

Self-Adhesive NPG-Edge® Intumescent with PVC Cover Self-Adhesive Silicone

- ▶ NPG-Edge® Sealing System/Smoke and Draft Control Gasketing Category "G" and "H" Classified
- ▶ NPG Intumescent Materials are Formulated to Expand at 375°F to 400°F Up To 8-10 Times Their Original Thickness; Completely Sealing the Gap Around and Between Doors During a Fire
- ▶ Moisture Resistant
- ▶ Modified Acrylic Pressure Sensitive Adhesive Protected by Release Liner
- ▶ Provides High Initial Adhesion and Long Term Holding Power for Permanent Mounting In Exterior or Interior Locations
- ▶ Resistant to Aging, Weathering, UV Radiation, Water, Detergent, Alcohol and the Influence of Chemicals
- ▶ End Use Temperature Range of Adhesive, Long Term Exposure -30°F Up To 250°F
- ▶ Shelf Life of Adhesive Prior to Installation is One Year When Stored at 75°F and 50% Relative Humidity or Less
- ▶ Rigid PVC Base with Flexible Elastomeric Bulb
- ▶ Flame Resistant
- ▶ Temperature Range -60°F to 275°F
- ▶ REACH and RoHS Compliant
- ▶ 1/8" Clearance Required Between Door and Frame
- ▶ 1 9/16" Wide x 5/64" + 1/4" Tall
- ▶ Available in 36", 48", 84", 96 and 108" Lengths



### Color

- 9500DKB x 2525B Brown
- 9500 x 2525B Gray x Brown
- 9500 x 2525W Gray x White



20, 45, 60, 90 minute rated category B  
 wood doors perimeter application up to:  
 single swing 4'0 x 9'0  
 pairs 8'0 x 9'0

NGP-GKT-9500X2525-PCS-1120-A