



# 9700

## Perimeter Seal



**BHMA**  
CERTIFIED



See [ngp.com](http://ngp.com) for  
All Applicable  
Certifications for  
this Product.



POSITIVE PRESSURE  
TESTED GASKETING  
MATERIALS FOR  
FIRE DOORS FOR  
APPLICATION TO  
HOLLOW-METAL-  
TYPE FIRE DOORS  
RATED UP TO 3  
HOURS AND WOOD-  
TYPE FIRE DOORS  
RATED UP TO  
1½ HOURS.  
CATEGORY H.

SMOKE AND  
DRAFT CONTROL  
GASKETING  
(CATEGORY H)  
TESTED TO UL  
1784; MEETS  
REQUIREMENTS  
OF NFPA 105, IBC  
FOR USE ON "S"  
LABEL DOORS.



[ngp.com](http://ngp.com)

1-800-NGP-RUSH

FAX:

(800) 255-7874

QUOTES:

[quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS:

[orders@ngp.com](mailto:orders@ngp.com)



## INSTALLATION INSTRUCTIONS

# 9700



**NOTE: Install seals before the closer.**

**Seals installed at head will require the closer body**

**be installed 1/4" lower on the door.**

**lower on the door.**

1. Cut seal to fit.
2. Drill head piece for mounting screws, avoiding the area where the closer shoe will be located.
3. With door closed, position seal with the gasketing slightly compressed against the door.
4. Install with TEK screws provided, working from one end to the other.

**ngp.com**

**1-800-NGP-RUSH**

FAX: (800) 255-7874

QUOTES: [quotes@ngp.com](mailto:quotes@ngp.com)

ORDERS: [orders@ngp.com](mailto:orders@ngp.com)