

9750

GAP SOLUTION FOR EXCESSIVE FIRE DOOR & FRAME CLEARANCES — 20 MINUTES UP TO 5/16"



UL CERTIFIED FOR USE IN
THE US AND CANADA

INTUMESCENT WITH FLEXIBLE ELASTOMERIC BULB FIRE AND SMOKE SEAL

- ▶ UL Certified Solution for 20-Minute Fire Doors with Excessive Clearance Between Door and Frame Over 1/8", up to 5/16"
- ▶ For Use on 20-Minute Rated UL10B and UL10C Wood or Hollow Metal Fire Doors
- ▶ Multiple Strike Shims 9275 or 9225 May Also be Required for Proper Latchbolt Engagement
- ▶ NGP Intumescent Materials are Formulated to Expand at 275°F up to 20 Times Their Original Thickness, Completely Sealing the Gap Around and Between Doors During a Fire
- ▶ Provides Strong Initial Adhesion and Outstanding Long-Term Holding Strength for Secure, Permanent Bonding in Both Interior or Exterior Applications
- ▶ Resistant to Aging, Weathering, UV Radiation, Water, Detergent, Alcohol, and the Influence of Chemicals
- ▶ Available in 36", 48", 84", 96" and 108" Lengths



Pictured:
9750C
(Charcoal)

9750 CHARCOAL

