



9750

INTUMESCENT WITH TPE FIRE AND SMOKE SEAL


PRODUCT CUT SHEET


PROJECT:
SUBMITTED BY:
DATE:
NOTES:

Material

Self-Adhesive Intumescent

- ▶ NGP-Edge® Sealing System/Smoke and Draft Control Gasketing Category “G” and “H” Classified
- ▶ NGP Intumescent Materials are Formulated to Expand at 375°F to 400°F Up To 8-10 Times Their Original Thickness; Completely Sealing the Gap Around and Between Doors During a Fire
- ▶ Moisture resistant
- ▶ BHMA Certified to ANSI/BHMA A156.22 Performance Tests for Heat and Cold
- ▶ Modified Acrylic Pressure Sensitive Adhesive Protected by Release Liner
- ▶ Provides High Initial Adhesion and Long Term Holding Power for Permanent Mounting in Exterior or Interior Locations
- ▶ Resistant to Aging, Weathering, UV Radiation, Water, Detergent, Alcohol and the Influence of Chemicals
- ▶ End Use Temperature Range of Adhesive, Long Term Exposure -30°F Up To 250°F
- ▶ Shelf Life of Adhesive Prior to Installation is One Year When Stored at 75°F and 50% Relative Humidity or Less
- ▶ Rigid PVC base with Flexible Elastomeric Bulb
- ▶ Flame Resistant
- ▶ Temperature Range -60°F to 275°F
- ▶ Anti-Microbial: Treated with an Anti-Microbial Additive to Inhibit the Growth of Microorganisms
- ▶ REACH and RoHS compliant
- ▶ 1/8" Clearance Required Between Door and Frame
- ▶ 1/2" Wide x 1/4" Tall
- ▶ Available in 36", 48", 84", 96 and 108" Lengths



 20, 45, 60, 90 minute rated category B wood doors perimeter application up to:
single swing 4'0 x 9'0
pairs 8'0 x 9'0

 STC.35

Color

9750B Brown
9750C Charcoal



NGP-GKT-9750-PCS-0720-A